# SAFETY DATA SHEET

1. Identification

Product number 1000006502

Product identifier 11 OZ RED GREASE 1420 LB 12PK
Company information SELECT SPECIALTY PRODUCTS

PO BOX 2026

CHARLOTTESVILLE, VA 22902-7227 United States

Company phone General Assistance 434-296-3937

Emergency telephone US 1-866-836-8855 Emergency telephone outside 1-952-852-4646

US

Version # 01

Recommended use Lubricant Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye

irritation. May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated

area. Wear eye/face protection.

Response If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting.

If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40

Chemical name	Common name and synonyms	CAS number	%
C12-C14 Isoalkanes		68551-19-9	20 - 40
Solvent naphtha (petroleum), light aliph.		64742-89-8	20 - 40
Carbon Dioxide		124-38-9	1 - 2.5
n-Heptane		142-82-5	0.1 - 1
Octane		111-65-9	0.1 - 1
Other components below reportable levels	S		10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

If eye irritation persists: Get medical advice/attention. Eye contact

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire-fighting

equipment/instructions

Specific methods

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Contaminants (29 CFR 1910.1 Type	Value	
<u> </u>			
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
Octane (CAS 111-65-9)	PEL	2350 mg/m3	
		500 ppm	
ACGIH			
Components	Туре	Value	
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 ppm	
US. ACGIH Threshold Limit Value			
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
·	TWA	5000 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
Octane (CAS 111-65-9)	TWA	300 ppm	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
,		250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
- (	3	440 ppm	
	TWA	350 mg/m3	

Product name: 11 OZ RED GREASE 1420 LB 12PK

SDS US

### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	
		85 ppm	
Octane (CAS 111-65-9)	Ceiling	1800 mg/m3	
		385 ppm	
	TWA	350 mg/m3	
		75 ppm	

#### **Biological limit values**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear suitable protective clothing.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

253.84 °F (123.24 °C) estimated

Flash point 193.6 °F (89.8 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 % estimated

(%)

Flammability limit - upper

7 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 191.38 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

SDS US

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

608 °F (320 °C) estimated **Auto-ignition temperature** 

**Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

0.476 estimated Specific gravity

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

### Information on likely routes of exposure

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be Inhalation

harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision.

### Information on toxicological effects

May be fatal if swallowed and enters airways. Narcotic effects. **Acute toxicity** 

,	,			
Components	nts Species Test Results			
Acetone (CAS 67-64-1)				
Acute				
Dermal				
LD50	Guinea pig	> 7426 mg/kg, 24 Hours		
		> 9.4 ml/kg, 24 Hours		
	Rabbit	> 7426 mg/kg, 24 Hours		
		> 9.4 ml/kg, 24 Hours		
Inhalation				
LC50	Rat	55700 ppm, 3 Hours		
		132 mg/l, 3 Hours		
		50.1 mg/l		
Oral				
LD50	Rat	5800 mg/kg		
		2.2 ml/kg		
n-Heptane (CAS 142-82-5)				
Acute				
Dermal				
LD50	Rabbit	> 2000 mg/kg, 24 Hours		

Product name: 11 OZ RED GREASE 1420 LB 12PK

Components	Species	Test Results
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Octane (CAS 111-65-9)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 24.88 mg/l, 4 Hours
Solvent naphtha (petroleum	), light aliph. (CAS 64742-89-8)	
Acute		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5020 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
Oral		3,
LD50	Rat	4820 mg/kg
2500	r cat	1020 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Not applicable.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

Product name: 11 OZ RED GREASE 1420 LB 12PK
Product #: 1000006502 Version #: 01 Issue date: 05-11-2015

Components Species Test Results

n-Heptane (CAS 142-82-5)

**Aquatic** 

Fish LC50 Mozambique tilapia (Tilapia 375 mg/l, 96 hours

mossambica)

Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

Aquatic

Algae IC50 Algae 4700 mg/L, 72 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 Acetone
 -0.24

 n-Heptane
 4.66

 Octane
 5.18

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**US RCRA Hazardous Waste U List: Reference** 

Acetone (CAS 67-64-1) U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

### 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

**UN proper shipping name** Aerosols, flammable

Product #: 1000006502 Version #: 01 Issue date: 05-11-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

LTD QTY

Not applicable.

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

**IMDG** 

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Benzene	71-43-2	0.01 - 0.1
Ethyl Benzene	100-41-4	0.01 - 0.1

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532

### **US** state regulations

### US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) n-Heptane (CAS 142-82-5) Octane (CAS 111-65-9)

### US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) n-Heptane (CAS 142-82-5) Octane (CAS 111-65-9)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) n-Heptane (CAS 142-82-5) Octane (CAS 111-65-9)

**US. Rhode Island RTK** 

Acetone (CAS 67-64-1)

# US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

Product #: 1000006502 Version #: 01 Issue date: 05-11-2015

### US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)

Toluene (CAS 108-88-3)

California Proposition 65 - CRT: Listed date/Female reproductive toxin

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009
US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

### 16. Other information, including date of preparation or last revision

**Issue date** 05-11-2015

Version # 01

United States & Puerto Rico

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Alternate Trade Names

Product name: 11 OZ RED GREASE 1420 LB 12PK

Product #: 1000006502 Version #: 01 Issue date: 05-11-2015 10 / 10

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).