SAFETY DATA SHEET

1. Identification

Product number	1000010818
Product identifier	18 OZ HANDY II 1494 LB 12PK
Company information	SELECT SPECIALTY PRODUCTS 1575 AVON STREET EXTENSION #104 CHARLOTTESVILLE, VA 22902-7227 United States
Company phone	General Assistance 434-296-3937
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	Cleaner
Recommended restrictions	None known.
2 Hazard(a) identification	

2. Hazard(s) identification

Physical hazards	Gases under pressure	Compressed gas
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
	$\wedge \wedge$	

Signal word Warning Contains gas under pressure; may explode if heated. Suspected of causing cancer. **Hazard statement Precautionary statement** Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. Collect spillage. Response Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal Hazard(s) not otherwise None known. classified (HNOC) Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Perchloroethylene		127-18-4	90 - 100
Carbon Dioxide		124-38-9	2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute a delayed	Dizziness. Headache. Nausea. Irritation of eyes and mucous membranes. Irritation of nose and throat. Skin irritation.
Indication of immediate medical attention and spec treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measu	ires
Suitable extinguishing me	dia Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
0	

Specific hazards arising from Contents under pressure. the chemical

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled equipment/instructions with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Fire-fighting

Cool containers exposed to flames with water until well after the fire is out.

6. Accidental release measures

Special protective equipment and precautions for firefighters

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

ccupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	

	Ту	nts (29 CFR 1910.100 pe		Value
				5000 ppm
US. OSHA Table Z-2 (29 C Components	CFR 1910.1000) Ty	ре	,	Value
Perchloroethylene (CAS 127-18-4)	Ce	iling	:	200 ppm
127 10 4)	TV	/A		100 ppm
US. ACGIH Threshold Lir Components	nit Values Ty	ре	,	Value
Carbon Dioxide (CAS 124-38-9)	ST	EL	:	30000 ppm
,	TV	/A	4	5000 ppm
Perchloroethylene (CAS 127-18-4)	ST	EL		100 ppm
,	TV		:	25 ppm
US. NIOSH: Pocket Guide Components	e to Chemical Hazard Ty	-	,	Value
Carbon Dioxide (CAS 124-38-9)	ST	EL	:	54000 mg/m3
124-30-9)			:	30000 ppm
	ΤV	/A		9000 mg/m3
				5000 ppm
ACGIH Biological Expose Components		Determinant	Specimen	Sampling Time
Components Perchloroethylene (CAS	ure Indices Value 0.5 mg/l	Determinant Tetrachloroethy	Specimen Blood	Sampling Time
Components	Value	Tetrachloroethy lene Tetrachloroethy	Blood End-exhale	*
Components Perchloroethylene (CAS 127-18-4)	Value 0.5 mg/l 3 ppm	Tetrachloroethy lene Tetrachloroethy lene	Blood	*
Components Perchloroethylene (CAS	Value 0.5 mg/l 3 ppm	Tetrachloroethy lene Tetrachloroethy lene	Blood End-exhale	*
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple	Value 0.5 mg/l 3 ppm ease see the source de	Tetrachloroethy lene Tetrachloroethy lene ocument.	Blood End-exhale	*
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, pla posure guidelines	Value 0.5 mg/l 3 ppm ease see the source do s: Skin designation a	Tetrachloroethy lene Tetrachloroethy lene ocument.	Blood End-exhale	* :d *
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple posure guidelines US - Minnesota Haz Subs Perchloroethylene (CA	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer	Tetrachloroethy lene Tetrachloroethy lene ocument. oplies Skin de ntilation (typically 10 a ed to conditions. If app ing controls to mainta	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev	* :d *
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, pla posure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matche or other engineer exposure limits h es, such as personal	Tetrachloroethy lene Tetrachloroethy lene ocument. oplies Skin de ntilation (typically 10 a ed to conditions. If app ing controls to mainta ave not been establish	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple posure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering htrols ividual protection measure	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer exposure limits h es, such as personal If contact is likely	Tetrachloroethy lene Tetrachloroethy lene ocument. oplies Skin de ntilation (typically 10 a ed to conditions. If app ing controls to mainta ave not been establish protective equipment	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt side shields ar	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple bosure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering htrols ividual protection measure Eye/face protection	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer exposure limits h es, such as personal If contact is likely	Tetrachloroethy lene Tetrachloroethy lene bocument.	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt side shields ar	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple posure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering htrols ividual protection measure Eye/face protection Hand protection	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer exposure limits h es, such as personal If contact is likely Wear appropriate	Tetrachloroethy lene Tetrachloroethy lene bocument.	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt side shields ar oves.	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, play bosure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering itrols ividual protection measure Eye/face protection Hand protection Skin protection	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer exposure limits h es, such as personal If contact is likely Wear appropriate	Tetrachloroethy lene Tetrachloroethy lene boument. pplies Skin de tilation (typically 10 a ed to conditions. If app ing controls to mainta ave not been establist protective equipment , safety glasses with s e chemical resistant gl	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt side shields ar oves.	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, ple posure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering htrols ividual protection measure Eye/face protection Hand protection Skin protection Other	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general ver should be matcher or other engineer exposure limits h es, such as personal If contact is likely Wear appropriate Use of an imperv	Tetrachloroethy lene Tetrachloroethy lene boument.	Blood End-exhale air esignation app in changes pe blicable, use p in airborne lev hed, maintain nt side shields ar oves. ended.	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio vels below recommended exposure limits. airborne levels to an acceptable level.
Components Perchloroethylene (CAS 127-18-4) * - For sampling details, play bosure guidelines US - Minnesota Haz Subs Perchloroethylene (CA propriate engineering htrols ividual protection measure Eye/face protection Hand protection Skin protection Other Skin protection	Value 0.5 mg/l 3 ppm ease see the source de S: Skin designation a AS 127-18-4) Good general very should be matche or other engineer exposure limits h es, such as personal If contact is likely Wear appropriate Use of an imperv If permissible levy air-supplied respi	Tetrachloroethy lene Tetrachloroethy lene boument.	Blood End-exhale air esignation app ir changes pe blicable, use p in airborne lev hed, maintain nt side shields ar oves. ended. NIOSH mech	* d * lies. r hour) should be used. Ventilation rates rocess enclosures, local exhaust ventilatio /els below recommended exposure limits. airborne levels to an acceptable level. e recommended.

9. Physical and chemical properties

Appearance

Dhusiaal state	Cas
Physical state	Gas.
Form	Aerosol. Compressed gas.
Color	Colorless.
Odor	Characteristic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	1.619 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Hydrogen chloride.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Dizziness. Headache. Nausea. Irritation of nose and throat. Irritation of eyes and mucous membranes. Skin irritation.
Information on toxicological effe	ects

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitizatior	ı	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	
Perchloroethylene (CAS 127-18-4) 2A Probably carcinogenic to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
US. National Toxicology Pro	ogram (NTP) Report on Carcin	ogens
Perchloroethylene (CAS	127-18-4)	Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	This product is not expected t	o cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of t	he product.
Chronic effects	Prolonged inhalation may be	harmful. Prolonged exposure may cause chronic effects.
12. Ecological information	1	
Ecotoxicity	Toxic to aquatic life with long	lasting effects.

Components		Species	Test Results	
Perchloroethylene (CA	S 127-18-4)			
Aquatic				
Crustacea	EC50	Daphnia	7.55 mg/L, 48 Hours	
		Water flea (Daphnia magna)	6.1 - 9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.82 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Partition coefficient n-octanol / water (log Kow)		
Perchloroethylene	3.4	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations


Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.	١.
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
US RCRA Hazardous Waste U List: Reference		
Perchloroethylene (CAS	27-18-4) U210	
Waste from residues / unused	Dispose of in accordance with local regulations. Empty containers or liners may retain some	

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
	on requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity.
Until 12/31/2020, the "Consum mark for packages of UN 1950	er Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and the IBC Code	





General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

• •			
US federal regulations	This product is a "Hazardous Standard, 29 CFR 1910.120 All components are on the U	0.	ed by the OSHA Hazard Communication
TSCA Section 12(b) Export	Notification (40 CFR 707, Sul	opt. D)	
Not regulated.			
CERCLA Hazardous Substa	nce List (40 CFR 302.4)		
Perchloroethylene (CAS SARA 304 Emergency relea		Listed.	
Not regulated. OSHA Specifically Regulate	ed Substances (29 CFR 1910.	1001-1050)	
Not listed.			
Superfund Amendments and Re	eauthorization Act of 1986 (SA	ARA)	
Hazard categories	Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No		
SARA 302 Extremely hazard	dous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name		CAS number	% by wt.
Perchloroethylene		127-18-4	90 - 100

Other federal regulations		
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List	
Perchloroethylene (CAS	127-18-4)	
Clean Air Act (CAA) Section	112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations		
US. Massachusetts RTK - S	ubstance List	
Carbon Dioxide (CAS 124 Perchloroethylene (CAS		
US. New Jersey Worker and	Community Right-to-Know Act	
Carbon Dioxide (CAS 124 Perchloroethylene (CAS	127-18-4)	
•	nd Community Right-to-Know Law	
Carbon Dioxide (CAS 124		
Perchloroethylene (CAS US. Rhode Island RTK	127-18-4)	
Perchloroethylene (CAS	127-18-4)	
US. California Proposition 6	,	
-	contains a chemical known to the State of California to cause cancer.	
US - California Proposit	ion 65 - CRT: Listed date/Carcinogenic substance	
Perchloroethylene (C	CAS 127-18-4) Listed: April 1, 1988	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	nents of this product comply with the inventory requirements administered by the go components of the product are not listed or exempt from listing on the inventory ad	

16. Other information, including date of preparation or last revision

Issue date Version #	02-06-2015 01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Alternate Trade Names