Section 1 Identification

Trade Name: DYNAMITE CONCRETE CLEAN

Product Identification: 7135

Synonyms: Granular alkali detergent

Product Use Description:

Concrete cleaner

General Info Phone: (800) 811-2987 Emergency Phone: (800) 535-5053

Supplier:

SELECT SPECIALTY PRODUCTS
1575 AVON STREET EXTENDED

SUITE 104

CHARLOTTESVILLE, VA 22901

Section 2 Hazards Identification

Classifications

Skin corrosion - Category 1

Eye Damage - Category 1

Specific Target Organ Toxicity (Single exposure) - Category 3



Signal Word: Danger

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Causes severe skin burns and eye damage

May cause respiratory irritation.

Precautionary Statements

Prevention

Do not breathe dusts. Use only in a well-ventilated area.

Wash hands thoroughly after handling.

Wear protective gloves and clothing.

Wear eye and face protection.

Keep only in original container.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower.

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center or a physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a poison center or a physician.

Storage

Store locked up.

Trade Name: DYNAMITE CONCRETE CLEANER SDS #: 7135 Page 1 of 5 SDS ID: SDS01112 Revision # 1 Revision Date 05/23/2015

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

		Concentiation
Chemical Name	<u>CAS #</u>	% by Weight
Sodium Metasilicate	6834-92-0	>=50 <= 60
Sodium Carbonate	497-19-8	>=10 <= 20
2-butoxyethanol	111-76-2	<= 1

Section 4 First Aid

EMERGENCY OVERVIEW

Concentration

DANGER. Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a poison center or a physician.

SKIN: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water/shower. If skin irritation persists get medical attention.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or a doctor.

INGESTION: Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

Section 5 Fire Fighting Measures

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

None known.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Trade Name: DYNAMITE CONCRETE CLEANER SDS #: 7135 Page 2 of 5 SDS ID: SDS01112 Revision # 1 Revision Date 05/23/2015

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods: Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Prevent runoff from entering drains, sewers, streams or other bodies of water. Sweep up and transfer contaminated product, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Avoid breathing dusts. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

2-butoxyethanol

ACGIH TLV 20 ppm OSHA PEL 25 ppm (skin)

Sodium Metasilicate

ACGIH TLV 10 mg/m3 OSHA PEL 15 mg/m3

Eye Protection: Wear safety glasses or goggles.

Skin Protection: Wear impervious gloves (made from rubber, nitrile or neoprene), clothing, and boots.

Respiratory Protection: When respiratory protection is required, use a respirator with particulate cartridge or dust mask. All

respiratory programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties

Property	<u>Value</u>		
Appearance	SOLID GRANULES	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Color	ORANGE (green when diluted)
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	NONE	Melting/Freezing Point	NOT AVAILABLE
Odor	SLIGHT BUTYL	Odor Threshold	NOT AVAILABLE
Other Information	VOC content (wt. %): 1.0	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	SOLID GRANULES
Relative Density	NOT APPLICABLE	Solubility (Water)	PARTIAL
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE
Viscosity	NOT AVAILABLE	рH	12-13

Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability: Stable under normal conditions.

Incompatible Materials: Acids and strong oxidizers

Conditions to Avoid: High temperatures

Decomposition Products: CO, CO2

Section 11 Toxicological Information

Trade Name:	DYNAMITE CONCRETE CLEANER	SDS #:	7135		Page 3 of 5
SDS ID:	SDS01112	Revision #	1	Revision Date	05/23/2015

Primary Route of Entry: Skin contact, eye contact, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling and possible tissue destruction.

INHALATION: Excessive exposure to dusts may irritate the mucous membranes and upper respiratory tract.

INGESTION: May be harmful or fatal if swallowed. Corrosive. Can cause severe burns and complete tissue perforation of

mucous membranes, mouth, throat and stomach.

Chronic / Long Term Effects: None known.

Target Organ Effects: Lungs and upper respiratory tract, gastrointestinal tract, eyes, skin.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Sodium Metasilicate: Oral - LD50, rat 1280 mg/Kg

Section 12 Ecological Information

Sodium Metasilicate:

LC50, Daphnia magna, 265-565 mg/l, 96 hr.

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 3262

Proper shipping name Corrosive Solid, Basic, Inorganic, n.o.s. (contains Sodium Metasilicate)

Class 8

Packing group ||

Section 15 Regulatory Information

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65)

2-butoxyethanol

If identified components of this product are CERCLA hazardous substances and/or listed under Sections 302, 304, or 313 of

Trade Name: DYNAMITE CONCRETE CLEANER SDS #: 7135 Page 4 of 5 SDS ID: SDS 01112 Revision # 1 Revision Date 05/23/2015

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic () Fire () Pressure () Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status:</u> Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

None

Section 16 Other Information

HMIS Ratings:



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/23/15

Trade Name: DYNAMITE CONCRETE CLEANER SDS #: 7135 Page 5 of 5 SDS ID: SDS01112 Revision # 1 Revision Date 05/23/2015