

G00353 MstSP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name

G00353 Mst SP Wire Rope Lube 45lb

Material number

000000000001002173

Manufacturer or supplier's details

Company

SUPPLIER:

Address

Select Specialty Products Inc.

1575 Avon St. Ext., Ste. 104 Charlottesville, Va 22902

Telephone

Emergency telephone numbers Compliance Services 1-877-428-9937

For SDS Information For a Medical Emergency 877-541-2016 Toll Free - All Calls Recorded For a Transportation CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	gel	
Colour	black	
Odour	oily, characteristic	

GHS Classification

Flammable liquids

: Category 3 Skin irritation Category 2 : Category 2A Eye irritation : Category 1 Aspiration hazard

GHS Label element

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

: Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/



G00353 MstSP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
asphalt	8052-42-4	>= 30 - < 50
Stoddard solvent	8052-41-3	>= 30 - < 50



G00353 Mst SP Wire Rope Lube 45lb

Version 1.0 Revision Date 06/02/2015 Print Date 09/22/2015

Distillates (petroleum), hydrotreated light	64742-47-8	>= 30 - < 50
Distillates (petroleum), hydrotreated heavy	64742-52-5	>= 1 - < 5
naphthenic		

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled

: If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

: If skin irritation persists, call a physician.

Wash off immediately with plenty of water for at least 15

minutes.

If on clothes, remove clothes.

In case of eye contact

: If in eyes, rinse with water for 15 minutes.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed

: Keep respiratory tract clear.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.



G00353 MstSP Wire Rope Lube 45lb

Version 1.0 Revision Date 06/02/2015 Print Date 09/22/2015

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : A

: Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

: No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid

: Incompatible materials

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters



G00353 Mst SP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Remarks

: The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection

: Ensure that eyewash stations and safety showers are close to

the workstation location.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection

: impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: gel

Colour

: black

Odour

: oily, characteristic

Odour Threshold

: no data available

На

: no data available



G00353 MstSP Wire Rope Lube 45lb

Version 1.0 Revision Date 06/02/2015 Print Date 09/22/2015

Melting point/freezing point

: no data available

Boiling point

: no data available

Flash point

: 43.3 °C

Evaporation rate

: not determined

Upper explosion limit

: no data available

Lower explosion limit

: no data available

Vapour pressure

: not applicable

Relative vapour density

: no data available

Density

: 0.862 g/cm3

Solubility(ies)

Water solubility

: negligible

Solubility in other solvents

: not determined

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature

: not determined

Thermal decomposition

: no data available

Viscosity

Viscosity, kinematic

: no data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: Stable

Chemical stability

: Stable under normal conditions.

Possibility of hazardous

reactions

: No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid

: Heat, flames and sparks.

Heat, flames and sparks.

Incompatible materials

: Oxygen

Hazardous decomposition

: Carbon oxides

products

Halogenated compounds

SECTION 11, TOXICOLOGICAL INFORMATION

Acute toxicity



G00353 Mst SP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

Components:

Distillates (petroleum), hydrotreated light:

Acute oral toxicity

: LD50 rat: > 5,000 mg/kg

Acute inhalation toxicity

: LC50 rat: > 4.6 mg/l

Exposure time: 6 h

Acute dermal toxicity

: LD50 rat: > 2,000 mg/kg

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity

: LD50 rat: > 5,000 mg/kg

Acute inhalation toxicity

: LC50 rat: > 5 mg/l

Exposure time: 4 h

Acute dermal toxicity

: LD50 rabbit: > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

asphalt:

Stoddard solvent:

Distillates (petroleum), hydrotreated light:

Distillates (petroleum), hydrotreated heavy naphthenic:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available



G00353 MstSP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

Distillates (petroleum), hydrotreated light:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

: Remarks: no data available

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: no data available

Components:

Distillates (petroleum), hydrotreated light:

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods



G00353 MstSP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

Waste from residues

: Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging

: Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):

UN1993, FLAMMABLE LIQUID, N.O.S., (HYDROTREATED LIGHT PETROLEUM DISTILLATES), 3,

Transportation Regulation: IATA (Cargo Air):

UN1993, Flammable liquid, n.o.s., (HYDROTREATED LIGHT PETROLEUM DISTILLATES), 3, III

Transportation Regulation: IATA (Passenger Air):

UN1993, Flammable liquid, n.o.s., (HYDROTREATED LIGHT PETROLEUM DISTILLATES), 3, III

Transportation Regulation: TDG (Canada):

NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: Acute Health Hazard

Fire Hazard

SARA 302

: SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313

: SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.



G00353 Mst SP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

California Prop 65

This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA

On TSCA Inventory

DSL

All components of this product are on the Canadian DSL.

AICS NZIoC PICCS

IECSC

Not in compliance with the inventory Not in compliance with the inventory

Not in compliance with the inventory Not in compliance with the inventory


Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	2	
FLAMMABILITY	2	
PHYSICAL HAZARD	0	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms







Signal w ord Hazard statements Danger:

Flammable liquid and vapour. May be fatal if sw allowed and enters airways. Causes skin irritation. Causes serious eye irritation.

Precautionary statements

Prevention: Keep aw ay from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/eye protection/face

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin w ith w ater/shower. IF IN EYES: Rinse cautiously w ith w aterfor several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and



G00353 Mst SP Wire Rope Lube 45lb

Version 1.0

Revision Date 06/02/2015

Print Date 09/22/2015

w ash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction

Storage: Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	06/02/2015
Print Date:	09/22/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.