SAFETY DATA SHEET

1. Identification

Product number 1000006488

Product identifier 16 OZ ALL ABOUT 2447 LB 12PK

02-24-2015 **Revision date**

SELECT SPECIALTY PRODUCTS **Company information** 1575 AVON STREET EXTENSION #104

CHARLOTTESVILLE, VA 22902-7227 United States

General Assistance 434-296-3937 Company phone

Emergency telephone US 1-866-836-8855 **Emergency telephone outside**

1-952-852-4646

Version # 03

02-03-2015 Supersedes date Recommended use Degreaser Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Skin corrosion/irritation Category 2 Serious eve damage/eve irritation Category 2A Sensitization, skin Category 1 Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. **Hazard statement**

May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs

Category 2

through prolonged or repeated exposure.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves. Wear

eye/face protection.

If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If in Response

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Specific treatment

(see this label). Do NOT induce vomiting. If skin irritation or rash occurs: Get medical

advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash before reuse. Collect spillage.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

classified (HNOC)

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Citrus Terpenes		94266-47-4	20 - 40
Butane		106-97-8	10 - 20
Propane		74-98-6	2.5 - 10
Diethanolamine		111-42-2	1 - 2.5
Diethylene Glycol Monoethyl Ether		111-90-0	1 - 2.5
Sodium Bicarbonate		144-55-8	1 - 2.5
Other components below reportable levels	6		40 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

In case of eczema or other skin disorders: Seek medical attention and take along these Skin contact

instructions.

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Dermatitis. Aspiration may cause pulmonary edema and pneumonitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

General information

media

Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

Value

1000 ppm

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)						
Components	Туре	Value				
Propane (CAS 74-98-6)	PEL	1800 mg/m3				

-	•				-
					1000 ppm

US.	ACGIH	Threshold	I imit	Values
oo.		IIIIESIIUIU		v alues

Components	Туре	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards Components Type

Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3
Propane (CAS 74-98-6)	TWA	3 ppm 1800 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides				
Components	Туре	Value		
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	TWA	140 mg/m3		

25 ppm

No biological exposure limits noted for the ingredient(s).

Biological limit values Exposure guidelines

US - California OELs: Skin designation

Diethanolamine (CAS 111-42-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) propellant estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.7 % estimated

Flammability limit - upper

(%)

6.1 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 23.88 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 458 °F (236.67 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Specific gravity 0.696 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

ctions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged

inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Dermatitis. Aspiration may cause pulmonary edema and pneumonitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

Butane (CAS 106-97-8) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes	Components	Species	Test Results
Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 M	Butane (CAS 106-97-8)		
LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 62 % 1355 mg/l	Acute		
Rat 1355 mg/l 1365 mg/l			
Rat	LC50	Mouse	1237 mg/l, 120 Minutes
Diethanolamine (CAS 111-42-2)			52 %, 120 Minutes
Acute Oral LD50		Rat	1355 mg/l
	Diethanolamine (CAS 111-4	42-2)	
LD50 Rat 1100 mg/kg Acute Dermal LD50 Guinea pig 5900 mg/kg, Days LD50 Rabbit 8500 mg/kg, 2 Hours 476 mg/kg, 24 Hours 7714 mg/kg LD50 Guinea pig 4970 mg/kg LD50 Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg Propane (CAS 74-98-6) 54 ml/kg Propane (CAS 74-98-6) 4237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 52 %, 120 Minutes	Acute		
Diethylene Glycol Monoethyl Ether (CAS 111-90-0) Acute Dermal LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg Oral LD50 Guinea pig 4970 mg/kg LD50 Mouse 6031 mg/kg Rabbit 5600 mg/kg 54 ml/kg Propane (CAS 74-98-6) 54 ml/kg Acute Inhalation 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes			
Acute Dermal 5900 mg/kg, Days LD50 Guinea pig 5900 mg/kg, 2 Hours Rabbit 8476 mg/kg, 24 Hours 7714 mg/kg 7714 mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg Fropane (CAS 74-98-6) Kat Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes	LD50	Rat	1100 mg/kg
Dermal LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg COral LD50 Guinea pig 4970 mg/kg LD50 Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg 5.4 ml/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Fat 1355 mg/l	Diethylene Glycol Monoethy	l Ether (CAS 111-90-0)	
LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg Oral The mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg Fropane (CAS 74-98-6) X Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes			
Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg Oral			
Section Sect	LD50	• •	
Oral LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg 5.4 ml/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes 1355 mg/l		Rabbit	
Oral LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg 5.4 ml/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes			8476 mg/kg, 24 Hours
LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Fat 5600 mg/kg 5.4 ml/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l			7714 mg/kg
Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg 5600 mg/kg 5.4 ml/kg Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l			
Rabbit 5600 mg/kg 5600 mg/kg 5600 mg/kg 5.4 ml/kg	LD50	Guinea pig	4970 mg/kg
Rat 5600 mg/kg 5.4 ml/kg		Mouse	6031 mg/kg
Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l		Rabbit	5600 mg/kg
Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse Rat Rat LC50 Rat Acute 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l		Rat	5600 mg/kg
Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l			5.4 ml/kg
Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l	Propane (CAS 74-98-6)		
LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes Rat 1355 mg/l			
52 %, 120 Minutes Rat 1355 mg/l	Inhalation		
Rat 1355 mg/l	LC50	Mouse	1237 mg/l, 120 Minutes
Ç			52 %, 120 Minutes
658 mg/l/4h		Rat	1355 mg/l
			658 mg/l/4h

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

SDS US

Species Test Results Components

Sodium Bicarbonate (CAS 144-55-8)

Acute

Oral

LD50 Rat > 4000 mg/kg

Causes skin irritation. Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Diethanolamine (CAS 111-42-2) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

exposure.

Respiratory system. Skin. Eyes. May cause damage to organs through prolonged or repeated

Toet Posulte

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause

damage to organs through prolonged or repeated exposure.

12. Ecological information

Components

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	lest Results
Diethanolamine (CAS	111-42-2)		
Aquatic			
Algae	IC50	Algae	7.8 mg/L, 72 Hours
Crustacea	EC50	Daphnia	55 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
Diethylene Glycol Mor	noethyl Ether (CAS	111-90-0)	
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours
Sodium Bicarbonate (CAS 144-55-8)		
Aquatic			
Crustacea	EC50	Daphnia	2350 mg/L, 48 Hours
Fish	LC50	Western mosquitofish (Gambusia affinis)	7550 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Butane 2.89 -1.43Diethanolamine Diethylene Glycol Monoethyl Ether -0.542.36 Propane

Mobility in soil No data available.

^{*} Estimates for product may be based on additional component data not shown.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards Yes ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed.

aircraft

Cargo aircraft only Allowed.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

Environmental hazards

 $\begin{tabular}{ll} \begin{tabular}{ll} \beg$

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

Not applicable.

LTD QTY

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diethanolamine (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value	

Ethylene Oxide 75-21-8 10 1000 lbs

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

CAS number	% by wt.	
111-42-2	1 - 2.5	
123-91-1	0.01 - 0.1	
75-21-8	0.01 - 0.1	
	111-42-2 123-91-1	111-42-2 1 - 2.5 123-91-1 0.01 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Diethanolamine (CAS 111-42-2)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Diethanolamine (CAS 111-42-2)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Diethanolamine (CAS 111-42-2)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

Diethanolamine (CAS 111-42-2)

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

 1,4-Dioxane (CAS 123-91-1)
 Listed: January 1, 1988

 Diethanolamine (CAS 111-42-2)
 Listed: June 22, 2012

 Ethylene Oxide (CAS 75-21-8)
 Listed: July 1, 1987

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Oxide (CAS 75-21-8) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene Oxide (CAS 75-21-8) Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene Oxide (CAS 75-21-8) Listed: August 7, 2009

Product #: 1000006488 Version #: 03 Revision date: 02-24-2015 Issue date: 06-30-2014

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS) European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

 Issue date
 06-30-2014

 Revision date
 02-24-2015

Version # 03

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Product Uses

Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information

GHS: Classification

Product name: 16 OZ ALL ABOUT 2447 LB 12PK

SDS US 10 / 10

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).