



# Select

Specialty Products

# INDUSTRIAL

## Aerosol Lubricants



# Select

Specialty Products

[www.sspva.com](http://www.sspva.com)  
**(800) 811-2987**



**LUBRA-GEL II - Stock #2413**  
 A high tack, clear, lubricating gel which provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Deposits a fine polytetrafluoroethylene and gel lubricant mixture deep inside working parts. Resists water washout and weathering.



**TEF LUBE II - Stock #1428**  
 A chemically inert, non-oily, fast-drying lubricant and release agent made with an extremely fine polytetrafluoroethylene powder. Features outstanding microscopic film-forming properties and resists temperatures from -100°F to +500°F. An odorless, stainless coating that is more slippery than silicone, graphite or oil. Excellent for reducing low speed friction.



**RED GREASE - Stock #1420**  
 Penetrates and lubricates difficult to reach surfaces (wire rope, cable, etc.) Air cures to an extra heavy duty grease that holds up under wide extremes of temperature (-40°F to +500°F) and extremes of pressure. Will not run or liquify under heat. Not washed away by water or steam.



**SLIX - Stock #1426**  
 A pure, non-staining super dry, heavy duty, multi-purpose silicone lubricant. Safe for use on almost any surface. Reduces friction and annoying squeaks in hinges, latches, springs, gears and other mechanisms.



**WHITE KNIGHT FOOD GRADE WHITE GREASE Stock #1432**  
 A ultra polymer structured White Food Grease with outstanding load carrying ability and superior high temperature resistance. Protects against rust, oxidation and wear and resists water and steam washout.



**KOOL KUT - Stock #1414**  
 Cutting Fluid formulated for all types of machine shop uses. This high performance coolant/lubricant increases production, protects tools, helps provide quality machine parts.



**ANTI-SEIZE COMPOUND - Stock #1401**  
 Prevents galling, seizing, pitting, fretting, corrosion and distortion of threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to 2100°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam.



**O.G.L. II - Stock #1408**  
 Sprays as an instant foaming, deep penetrating liquid that flows inside intricate chains and cables where the greatest stress occurs. Provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope and roller chain mechanisms.



**DRI-MOL - Stock #1405**  
 An extreme range lubricant and anti-seize coating that withstands temperatures from -110°F to +1050°F. Resists pressures up to 100,000 psi. Inert to water, oil, alkalis and many acids. Dry film coating will not attract dirt or dust. Provides lubrication even under salt spray conditions.



**ANTI-SEIZE II - Stock #1495**  
 Prevents galling, seizing and galvanic action. Protects against rust and corrosion. Will not wash off. Assured long-term protection with one application, outdoors or indoors, even in damp areas or against salt spray. Will not evaporate, separate or harden. Will not fuse to metals

