Select
Specialty Products

PENETRANTS &
Lubricants

NO CFCs
CONTAINS NO CFC WHICH DEPLETE THE OZONE LAYER

STEEL

Select
Specialty Products
FREE ALL
STOCK #1407

PENETRANT • LUBRICANT
DEMOISTURANT • PROTECTANT

• NON-CHLORINATED
• NON-FLAMMABLE SPRAY
• PENETRATES — CLEANS
• FREES FROZEN FITTINGS
• 30,000 VOLT DIELECTRIC STRENGTH
• NEVER DRIES
• LUBRICATES
• DISPLACES WATER

NET WT. 12 OZ. (340 Grams)

CAUTION:
VAPOR HARMFUL
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON BACK PANEL

Select
Specialty Products
NO DOUBT
Stock #2480

PENETRANT
LUBRICANT
DEMOISTURANT
PROTECTANT

NON-FLAMMABLE SPRAY
FAST PENETRATING ACTION
HIGH DIELECTRIC STRENGTH

NET WT. 18 OZ. (1 LB. 2 OZ.) (510 Grams)

DANGER:
VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

Select
Specialty Products
RUST FREE
Stock #1475

PENETRATING
LUBRICANT

• PENETRATES AND DISSOLVES
RUST AND CORROSION
• EXCELLENT CREEP CHARACTERISTICS
• CONTAINS MOLY and PTFE
• FEATURES A 360° VALVE

NET WT. 11 OZ. (311 Grams)

DANGER:
EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

Select
Specialty Products
NEW! IMPROVED!
LUBRA-GEL II
with PTFE
STOCK #2413
Penetrating Lubricant Gel

• NON CHLORINATED • WATER RESISTANT
• EFFECTIVE IN EXTREME TEMPERATURES
• BURNISHES PTFE COATING INTO
WORKING PARTS

EXCELLENT ON: • Door Hinges • Open
Gears • Wire Ropes • Cables • Chains &
Sprockets • Conveyors • Legs on Hoists

NET WT. 12 OZ. (340 Grams)

DANGER:
EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF
SWALLOWED. CONTENTS UNDER PRESSURE. SEE
OTHER CAUTIONS ON BACK PANEL.

Select
Specialty Products
RED GREASE
STOCK #1420

PENETRATING LIQUID
LUBRICANT

AIR CURES TO A HIGH TEMPERATURE
HIGH PRESSURE GREASE

NET WT. 11 OZ. (311 Grams)

DANGER:
EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
VAPOR HARMFUL
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON BACK PANEL

Select
Specialty Products
O.G.L. II
STOCK #1408

FOAMING
GEAR AND CHAIN
LUBRICANT

Protectant Fortified with Moly

Prevents Corrosion

High Pressure and
Extreme Temperature Resistance

Withstands Harsh
Chemical Environments

NET WT. 15 OZ. (425 Grams)

CAUTION:
FLAMMABLE
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON BACK PANEL

Charlottesville, VA 22902 • (800) 811-2987 • www.sspva.com

NO DOUBT - Stock #2480
A fast-acting PENETRANT that quickly cuts through dirt, rust and scale to creep into parts which have become frozen by or encrusted with corrosion and oxidation. Provides a long-lasting LUBRICANT which loosens dirt, rust and other corrosive elements, reduces friction and will not become dry, brittle or hard.

RUST FREE - Stock #1475
A unique concentrated formula containing micron sized particles of Molybdenum Disulfide and Tetrafluoroethylene. Forceful jet spray aids in penetrating thru rust and corrosion to free frozen parts. Stops annoying squeaks.

O.G.L - Stock #1408
Provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope and roller chain mechanisms. Protects against high temperature and extreme pressure environments. Grease will not break down, fly off or wash away with water or steam.

RED GREASE - Stock #1420
Penetrates and lubricates difficult to reach surfaces (wire rope, cable, etc.) Air cures to an extra heavy duty grease that holds up under wide extremes of temperature (-40°F to +500°F) and extremes of pressure. Will not run or liquify under heat. Not washed away by water or steam.

LUBRA-GEL II - Stock #2413
A high tack, clear, lubricating gel which provides lubrication at temperatures from –30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film.

FREE ALL - Stock #1407
Penetrates through rust and scale to loosen parts which have been frozen by corrosion. Lubricates parts to ensure free and easy movement. Demoisturizes and creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge. Protects and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.